



Faculty of Manufacturing Engineering

DEVELOPMENT OF KENAF POLYMER COMPOSITE SANDWICH STRUCTURE

Nurul Farah Adibah binti Mohd

Master of Science in Manufacturing Engineering

2015

**DEVELOPMENT OF KENAF POLYMER COMPOSITE SANDWICH
STRUCTURE**

NURUL FARAH ADIBAH BINTI MOHD

**A thesis submitted
in fulfilment of the requirements for the degree of Master of Science
in Manufacturing Engineering**

Faculty of Manufacturing Engineering

UNIVERSITI TEKNIKAL MALAYSIA MELAKA

2015

DECLARATION

I declare that this thesis entitled “Development of Kenaf Polymer Composite Sandwich Structure” is the result of my own research except as cited in the references. The thesis has not been accepted for any degree and is not concurrently submitted in candidature of any other degree.

Signature :.....

Name :.....

Date :.....

APPROVAL

I hereby declare that I have read this thesis and in my opinion this thesis is sufficient in terms of scope and quality for the award of Master of Science in Manufacturing Engineering.

Signature :.....

Supervisor Name :.....

Date :.....

DEDICATION

For my beloved family:

HUSBAND

FATHER

MOTHER

SIBLINGS

For my adored supervisor and co-supervisor:

Dr. Taufik

Professor Madya Engr. Dr. Hambali bin Arep@Ariff

ABSTRACT

This research presents the development of kenaf polymer composite sandwich structure. The aim of this research is to propose natural fibre composites to be introduced in metal matrix composites material for further manufacturing processes. The core natural fibre material used is kenaf fibre while polyester and polypropylene act as matrix materials. LM6 material was selected as metal matrix composites and used as the skin of sandwich layers for simulation study. Two types of composite processes had been used in this research, hand lay-up process for application of polyester and hot moulding process for polypropylene application. These two types of laminate composite have been tested to analyse the mechanical properties and thermal properties. Based on the testing results, kenaf-polyester composite had been chosen as the proposed material to be applied to the sandwich model. The natural fibre composites were tested by mechanical and thermal testing procedures to meet the ASTM requirements. There were 5 types of ASTM standard has been used in this research such as ASTM D3039, ASTM D638-99, ASTM D7624, ASTM D790 and ASTM E794-01. Tensile test, flexural test, and thermal test had been used in this research. Five specimens were prepared for tensile test and flexural test, followed by one specimen for each laminate composite in thermal test. Thermal test procedure had been prepared by using DSC (Differential Scanning Calorimetric) method. The results showed the polyester was the optimum material to be used as the matrix material for laminate composite due to the high tensile and flexural strength as well as high in the value of maximum force. The DSC test result shows the greater melting temperature in polyester as compared to polypropylene. Furthermore, the LM6 model and sandwich model were designed by using SolidWorks simulation to determine the stress distribution, displacement distribution and factor of safety. As a result, kenaf-fibre polyester composite as core layer in sandwich model of LM6 was potential to be applied for engineering application.

ABSTRAK

Kajian ini membentangkan pembangunan struktur sandwich komposit polimer kenaf. Tujuan kajian ini adalah untuk mencadangkan komposit serat semulajadi yang akan diperkenalkan dalam bahan komposit logam matriks untuk proses pembuatan yang mendatang. Bahan serat semulajadi teras yang digunakan adalah gentian kenaf manakala polyester dan polipropilena bertindak sebagai bahan matriks. Bahan LM6 telah dipilih sebagai komposit matriks logam dan digunakan sebagai kulit lapisan sandwich untuk kajian simulasi. Dua jenis proses komposit telah digunakan dalam penyelidikan ini iaitu tangan proses hand lay-up untuk digunakan daripada bahan polyester dan proses pengacuan panas untuk digunakan oleh polipropilena. Kedua-dua jenis lamina komposit telah diuji untuk menganalisis sifat-sifat mekanikal dan sifat haba. Berdasarkan kepada keputusan ujian, kenaf-poliester komposit telah dipilih sebagai bahan yang dicadangkan untuk digunakan bagi model sandwic. Komposit serat semulajadi telah diuji oleh prosedur ujian mekanikal dan haba untuk memenuhi keperluan ASTM. Terdapat 5 jenis ASTM standard telah digunakan dalam kajian ini seperti ASTM D3039, ASTM D638-99, ASTM D7624, ASTM D790 dan ASTM E794-01. Ujian tegangan, ujian lenturan, dan ujian terma telah digunakan dalam kajian ini. Lima specimen disediakan untuk ujian tegangan dan ujian lenturan, diikuti dengan satu specimen untuk setiap lamina komposit dalam ujian terma. Prosedur ujian Thermal telah disediakan dengan menggunakan kaedah DSC (Pengimbasan Perbezaan kalorimetri). Keputusan menunjukkan polyester adalah bahan yang optimum untuk digunakan sebagai bahan matriks untuk lamina komposit kerana kekuatan tegangan yang tinggi dan lenturan serta tinggi dalam nilai daya maksimum. Keputusan ujian DSC menunjukkan suhu lebur yang lebih besar dalam polyester berbanding dengan polipropilena. Tambahan pula, model sandwich dan model LM6 telah direka dengan menggunakan SolidWorks simulasi untuk menentukan taburan tekanan, pengedaran anjakan dan factor keselamatan. Hasilnya, kenaf serat komposit polyester sebagai lapisan teras dalam model sandwich LM6 berpotensi untuk digunakan bagi aplikasi kejuruteraan.

ACKNOWLEDGEMENT

Alhamdulillah and Thank to Allah S.W.T. with all His Gracious and His Merciful for giving me strength and ability to accomplish this project successfully. I would like to take the utmost opportunity to express my sincere and gratitude to my supervisor, Dr. Taufik that always giving me supports and guidance throughout the year in completing this Master thesis. Besides, thanks a lot to all lecturers of Faculty of Manufacturing Engineering especially to my co-supervisor, Professor Madya Engr. Dr. Hambali bin Arep@Ariff.

Also with the greatest thanks to my beloved husband, parents and family which always pray and give the encouragement while pursuing my research and thesis writing. Their sacrifices are never being forgotten.

I also would like to convey my biggest appreciation to all the technicians in Manufacturing Engineering Faculty Laboratory for helping and supporting me in accomplishes this Master Research without hesitation. All the knowledge and experience I gained would not be forgotten.

Last but not least, to all my fellow friends who involves direct or indirectly that always stand strong beside me in giving opinions and supports throughout our relationship, I really thankful and appreciate it. All yours are the most valuable things for rest of my life.

TABLE OF CONTENTS

	PAGE
DECLARATION	
APPROVAL	
DEDICATION	
ABSTRACT	i
ABSTRAK	ii
ACKNOWLEDGEMENTS	iii
TABLE OF CONTENTS	iv
LIST OF TABLES	vii
LIST OF FIGURES	viii
LIST OF SYMBOLS	xii
LIST OF APPENDICES	xiii
LIST OF ABBREVIATIONS	xiv
LIST OF PUBLICATIONS	xvi
 CHAPTER	
1. INTRODUCTION	1
1.1 Background	1
1.2 Problem Statement	3
1.3 Research Objectives	4
1.4 Scope of Research	4
 2. LITERATURE REVIEW	6
2.1 Introduction of Composites	6
2.1.2 Composites Classification	7
2.2 Natural Fibres Composite	9
2.2.1 The Advantages of Natural Fibre Composites	10
2.3 Matrix Materials	13
2.3.1 Thermosets	13
2.3.1.1 Polyester Resin	15
2.3.2 Thermoplastics	17
2.3.2.1 Polypropylene	19
2.4 Reinforcement Materials	19
2.4.1 Kenaf Fibre	20
2.4.1.1 Mechanical Properties of Kenaf	23
2.5 Fabrication Process	25
2.5.1 Hand Lay-up Process	26
2.5.2 Compression Moulding and Internal Mixing	27
2.6 Mechanical Properties	29
2.6.1 Stress and Strain	29
2.6.2 Elasticity and Plasticity	29
2.6.3 Tensile and Ductility	30
2.6.4 Toughness	31
2.7 Thermal Analysis	31
2.7.1 Determination of Glass Transition Temperature	32
2.7.2 Determination of Melting temperature	33
2.8 Sandwich Design	34

2.9	LM6 Aluminium Alloy	37
2.10	Design Tools	39
2.10.1	SolidWorks 2009	39
2.10.2	SolidWorks Simulation	39
2.9	Importance of Research	41
3.	METHODOLOGY	44
3.1	Introduction to Methodology	44
3.2	Flow Chart	45
3.3	Materials	46
3.3.1	Polyester Resin	46
3.3.2	Polypropylene	47
3.3.3	Kenaf Fibre	48
3.3.4	LM6 Aluminium Alloy	49
3.4	Fabrication Method	50
3.4.1	Hand Lay-up	51
3.4.2	Compression Moulding	52
3.5	Experimental Analysis	53
3.5.1	Tensile Test	53
3.5.1.1	Step-wise Procedure for Tensile Test	57
3.5.2	Flexural Test	57
3.5.2.1	Step-wise Procedure for Flexural Test	58
3.5.3	Differential Scanning Calorimetry Test	59
3.5	Sandwich Design	61
4.	RESULT AND DISCUSSION	67
4.1	Hand Lay-up Specimens	67
4.2	Internal Mixing Specimens	67
4.3	Specimens for Material Testing	68
4.4	Tensile Test	69
4.4.1	Tensile Strength of Polymer and Kenaf-polyester Composite	70
4.4.2	Tensile Strength of Polypropylene and Kenaf-polypropylene Composite	71
4.4.3	Maximum Force of Composites for Tensile Test	72
4.5	Flexural Test	73
4.5.1	Flexural Strength	74
4.5.2	Maximum Force for Flexural Test	75
4.6	Differential Scanning Calorimetry Test	76
4.7	Simulation Study	78
4.7.1	LM6 Model	79
4.7.2	Sandwich Model	86

5.	CONCLUSION AND DISCUSSION	95
5.1	Conclusion	95
5.2	Recommendation	97
	REFERENCES	99
	APPENDICES	107

LIST OF TABLES

TABLE	TITLE	PAGE
2.1	Characteristic values for the density, diameter, and mechanical properties of natural plant and synthetic fibres	11
2.2	Comparison between epoxy and polyester	17
2.3	Properties of filled/reinforced polypropylene composite	22
2.4	Advantages and disadvantages of hand lay-up process	27
2.5	LM6 aluminium alloy chemical composition	38
3.1	Characterization of UPR	46
3.2	Characterization of MEKP	47
3.3	Chemical Analysis Data of Kenaf Core and Bast Fibres	48
3.4	LM6-M (A413.2) properties	50
3.5	ASTM standard for mechanical test	53
3.6	Dimensions of specimen for tensile test ASTM D638-99	55
3.7	Rectangular shaped specimen Dimension in ASTM D3039	55
3.8	Mass of sample compared to reference material	60
4.1	Summary of simulation study	94

LIST OF FIGURES

FIGURE	TITLE	PAGE
2.1	Composite compositions	7
2.2	Composites categories	8
2.3	Classification of natural fibres	10
2.4	Cross link of thermoset	14
2.5	Thermoplastic cross link	18
2.6	Kenaf plants	20
2.7	Hand lay-up process	26
2.8	Compression moulding process	28
2.9	The difference between elasticity and plasticity	30
2.10	Heat flow rate measured by DSC showing the practical determination of T _g	32
2.11	DSC curve for semi-crystalline polymer showing melting temperature	33
2.12	Typical sandwich composites	35
2.13	Schematic view of sandwich sheet	37
2.14	The design process uses CAD and FEA as design tools	40
3.1	Methodology Flowchart	45
3.2	Polypropylene in pallet size	47
3.3	Vibratory sieve-shaker	49

3.4	Mould size for hand layup process	51
3.5	Rectangular tension test specimen for kenaf-polypropylene composite	55
3.6	Rectangular shape specimen dimension in accordance with ASTM D3039 for kenaf-polyester composites.	56
3.7	Universal Testing Machine, UTM AGI 100 KN from Shimadzu for Tensile and Flexural testing	56
3.8	Requirement range of loading nose and support radii in ASTM D790	58
3.9	The working of DSC machine	60
3.10	Drawing for LM6 model	62
3.11	Drawing for sandwich design	63
3.12	Quarter point loading	64
3.13	Force and fixed geometry location for LM6 model (Isometric view)	65
3.14	Force and fixed geometry location for LM6 model (Front View)	65
3.15	Force and fixed geometry location for sandwich design (Isometric view)	66
3.16	Force and fixed geometry location for sandwich design (Front view)	66
4.1	Specimen for tensile test, a) 100wt% polyester, b) 50-50wt% kenaf-polyester composite	68
4.2	Specimens for tensile test, a) kenaf-polypropylene composite, b) 100wt% polypropylene	69

4.3	Specimens for flexural test a) 100wt% polypropylene composite, b) kenaf-polypropylene composite c) kenaf-polyester composite	69
4.4	Graph of tensile strength for polyester and kenaf-polyester composite	71
4.5	Graph of tensile strength for polypropylene and kenaf-polypropylene composite	72
4.6	Graph of maximum force for kenaf-polyester composite and kenaf-polypropylene composite	73
4.7	Graph of flexural strength for kenaf-polyester composite and kenaf-polypropylene composite	74
4.8	Graph of flexural strength for kenaf-polyester composite and kenaf-polypropylene composite	75
4.9	DSC graph for kenaf-polypropylene composite	77
4.10	DSC graph for kenaf-polyester composite	78
4.11	Static Nodal Stress of LM6 model	79
4.12	Section clipping of stress at centre for LM6	80
4.13	Section clipping of stress at force point for LM6	80
4.14	Section clipping of stress at fixed geometry point for LM6	81
4.15	Static displacement of LM6 model	81
4.16	Section clipping of displacement at centre for LM6	82
4.17	Section clipping if displacement at force point for LM6	83
4.18	Section clipping of displacement at fixed geometry point for LM6	83

4.19	Factor of safety distribution of LM6 model	83
4.20	Section clipping for factor of safety at centre	85
4.21	Section clipping for factor of safety at force point	85
4.22	Section clipping for factor of safety at fixed geometry location	85
4.23	Static Nodal Stress of sandwich model	86
4.24	Section clipping of stress at centre for sandwich model	88
4.25	Section clipping of stress at force point for sandwich model	88
4.26	Section clipping of stress at fixed geometry point for sandwich model	88
4.27	Static displacement of sandwich model	89
4.28	Section clipping of displacement at centre for sandwich model	90
4.29	Section clipping of displacement at force point for sandwich model	91
4.30	Section clipping of displacement at fixed geometry point for sandwich model	91
4.31	Factor of safety distribution of sandwich model	91
4.32	Section clipping of factor of safety at centre for sandwich model	92
4.33	Section clipping of factor of safety at force point for sandwich model	93
4.34	Section clipping of factor of safety at fixed geometry point for sandwich model	93

LIST OF SYMBOLS

%	-	percent
MPa	-	Mega Pascal
GPa	-	Giga Pascal
T _g	-	Glass transition temperature
T _m	-	Melting temperature
T _{use}	-	Temperature which is used
°C	-	Degree Celsius
Wt%	-	Weight percentage
~	-	Approximate
g	-	Gram
μm	-	Micrometer
cm	-	Centimetre
mm	-	millimetre
MJ	-	Mega Joule
s	-	second
kg	-	kilogram
kN	-	Kilo newton
min	-	minute

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Gantt Chart	108
B	Equipment and Methods	110
C	Result for mechanical test	115

LIST OF ABBREVIATIONS

DfS	-	Design for Sustainability
OPEFB	-	Oil palm empty fruit bunch
PMC	-	Polymer matrix composite
ASTM	-	American standard testing method
MMC	-	Metal matrix composite
CMC	-	Ceramic matrix composite
UP	-	Unsaturated polyester
UPR	-	Unsaturated polyester resin
PP	-	Polypropylene
DSC	-	Differential scanning calorimetry
TMA	-	Thermomechanical analysis
DMA	-	Dynamic mechanical analysis
DEA	-	Dielectric analysis
PEEK	-	Polyether ether ketone
FRP	-	Fibre reinforced composite
CAD	-	Computer aided design and drafting
CADD	-	Computer aided design
3D	-	3 dimensional
2D	-	2 dimensional
FEA	-	Finite element analysis

MEKP	-	Methyl ethyl ketone peroxide
GMT	-	Glass mat thermoplastic
AE	-	Acoustic emission
Si	-	silicon
Al	-	aluminium
HV	-	Hardness Vickers
UTM	-	Universal testing machine

LIST OF PUBLICATIONS

Nurul, F.A.M., Taufik, R.S., and Mohammad, H.A.K., 2014. Feasibility Study of Casted Natural Fibre-LM6 Composites for Engineering Application. *Advanced Materials Research*, 903, pp. 67-72.

(International Manufacturing Engineering Conference [IMEC 2013])

Hafizudin, M., Taufik, Razali, M., Nurul, F.A.M., 2014. Surface Roughness of Casted LM6 Using Natural Fibre Sand Casting Mould. *Advanced Materials Research*, 903, pp. 78-82.

(International Manufacturing Engineering Conference [IMEC 2013])

Taufik, R.S., Nurul, F.A.M., Muhamad, M.R., Hasib, H., 2014. Feasibility Study of Natural Fibre Composite Material for Engineering Application. *Journal of Mechanical Engineering and Sciences*, 6, pp. 940-948.

(International Conference on Mechanical Engineering Research [ICMER 2013])

Nurul, F.A.M., Taufik, R.S., and Mohammad, H.A.K., 2015. Simulation Study on Kenaf-fibre Polyester Composite and LM6 Material. *Applied Mechanics and Materials*, 761, pp. 584-588.

(International Conference on Design and Concurrent Engineering [iDECON 2014])

Mohammad, H., Taufik, R.S., Mohd, R.M., Nurul, F.A.M., Kamal, M.R., 2015. Mechanical Properties of Oil Palm Empty Fruit Bunch Fibres-Cast Alloy Composite using Three Point Bending Test. *Applied Mechanics and Materials*, 761,pp. 374-379. (International Conference on Design and Concurrent Engineering [iDECON 2014])

CHAPTER 1

INTRODUCTION

1.1 Background

The development of natural fibre composites have been attracting researchers to offer more attention due to their effective cost, reasonably fine mechanical properties, non-abrasive and biodegradable types (Ku et al., 2011). Daniel and Suong (2003) stated composite material is different from common heterogeneous materials. According to Kaw (2005), composite is a structural material that consists of two or more joint constituents. They are combined each other at a macroscopic level and are soluble. One constituent is known as filler and the other one is known as matrix. Armstrong et al. (2005) highlighted that composites are combinations of materials which differing in composition or form where the entity constituent retain their separate identities and do not dissolve or merge together. Application of composite materials represented as 70 % of market value, 23 % automotive, 21 % public work, 23 % building, 17 % aeronautics and 11 % sport as studied by Shakila (2006).

Natural fibre composite is widely discussed in various manufacturing industries due to their relatively low material cost and potential to reduce the overall production cost, without compromising the design requirements, and customer satisfaction. There are various applications in order to increase the strength ratio and flexibility in designing of products. Natural fibre composite is one of the preferred approaches. These natural fibres

have various properties which make the natural fibre an attractive alternative material. Most of researchers have been exploring on the potential of high specific properties and advantages of natural fibre such as its quality in stiffness (Sherman, 1999), impact resistance (Sydenstricker et al., 2000), flexibility (Manikandan et al., 1996), modulus elasticity (Eichhorn et al., 2001), and renewable capability. Natural fibres can be classified into three categories which are bast, seed and leaf (Sgriecia et al., 2008). The design of natural fibre composites involves fabricating the physical specimens for analysis on the microstructures of natural fibre product and study on their mechanical properties. Exploration of the use of natural fibre composite materials and what type of natural fibre composite needs to be further investigated particularly in designing of production tooling.

The application of design for sustainability faces various challenges in manufacturing. The most outstanding challenges which to be resolved is to contribute to the alteration in the direction of a sustainable society by integrating some aspect such as economic, social, ecological and institutional by contribution opportunities to express one's own identity further than consuming standardized mass products. Several design methodology have been recently proposed in order to study the feasibility of using angles of design, sustainability science and sustainable consumption analysis, developing tools and rules to support Design for Sustainability (DfS) (Joachim et al., 2010). Besides that, the design methodology systems analysis perspective is to extend the conventional process design structure to green process design, green energy and industrial ecology leading to sustainability (Urmila and Yogendra, 2010). The green process design starts with the design decisions by considering chemical and materials variety stages at one end which planning and managing decisions at the other end. Nevertheless, uncertainties and multiple and conflicting objectives are inherent in such a design process. Uncertainties enhance further in industrial natural science.